

Inspired Floorcoverings

Carpet Tile Installation

Guide

Installed in accordance
with AS2455.2:2019

1. Each tile has directional arrows on the backing. This allows for one-directional or multi-directional installation. NOTE: Lineal patterns when installed directional may produce an undesired effect when lines of the same colour meet on two edges. Installers need to monitor this during installation and reposition tiles where appropriate. Patterns that are random in nature may contain additional colour ways to the ones displayed on the samples. Please consult your Inspired Floorcoverings sales consultant for further information.
2. Installation must begin at the intersection of two chalk lines. Installation must continue until completed in one quadrant, and then proceed to an adjoining quadrant until all four quadrants are completed.
3. Install modules using the pyramid technique. This allows multiple alignment checks. If the edges do not align and the misalignment increases with progression of the installation, the source of the problem must be identified and corrected.
4. Slide tiles into position to prevent yarn from being trapped between the tiles. Trapped yarn will adversely affect the appearance of the installation and will cause alignment problems.
5. Tile must fit snugly, but not be compressed. Check for fit by measuring the length of ten (10) full tiles after installation. The measurement must not be less than, or exceed by more than 6mm, the length of the tiles being multiplied by ten (10) For example: if 500mm X 500mm tiles are being installed, the measurement should be between 5000mm and 5006mm. Post installation care ♣ Roll the entire installation with a 35kg roller once it is completed. ♣ Use plywood over the carpet when heavy objects are moved within the next 24 hours after ♣ Protective chair mats under chairs with casters are recommended. This will prevent excessive wear to the face and possible transfer of the pressure sensitive adhesive to the back of the carpet.

Recommended Adhesive

PVC backed tiles = Standard PS Carpet Tile Adhesive

Cushion back tiles = Hi Tack PS Adhesive

Application by roller is approved for PVC backed tiles

Application by V Notch trowel for cushion backed tiles.