



Inspired Floorcoverings
 PO Box 575 Terrigal, NSW. 2260

TECHNICAL SPECIFICATIONS
Flinders Range
Australian Stone Collection

	Standard	Results
Plank Size:		457mm x 457mm
Thickness:		2.55mm
Wear Layer:		0.55mm
Slip Rating:	AS/NZS 4586:2004 (Appendix D)	R10 (High)
Fire Rating:	Average Critical Radiant Flux Average Integrated Smoke Value	10.7 kW/m ² 41%.min
Warranty:	Commercial Domestic	15 years* 20 years*
Bevelled Edge:		Yes
Classification:	Commercial Domestic	Heavy Duty Use Heavy Duty Use
Standards:	EN 649 ISO 14001 ISO 9001	Pass Pass
Abrasion Resistance:	EN660	Group T
Stain Resistance:	EN 423	Excellent
Colour Fastness To Light:	ISO 105-B02	7 or better Exceed Requirements
Dimensional Stability:	EN 434	0.15%
Sound Reduction:	DIN52210	8dB
Point Load Resistance:	EN 433	Pass
Caster Chair Continuous Use:	EN 425	Pass
Thermal Resistance:	DIN 52612	0.026Km ² Underfloor Heating Suitable
Recycling:		Suitable